

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0001 3-91 - Chloroprene Unit - Fugitive Emissions

- 282 [40 CFR 63.180] Comply with the test methods and procedures requirements provided in 40 CFR 63.180. Subpart H.
- 283 [40 CFR 63.181] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Maintain records as specified in 40 CFR 63.181(a) through (k). Subpart H.
- 284 [40 CFR 63.182(b)] Submit Initial Notification: Due within 120 days after the date of promulgation of the subpart that references 40 CFR 63 Subpart H. Include the information specified in 40 CFR 63.182(b)(1). Subpart H. [40 CFR 63.182(b)]
- 285 [40 CFR 63.182(c)] Submit Notification of Compliance Status: Due within 90 days of the compliance dates specified in the 40 CFR 63 subpart that references 40 CFR 63 Subpart H. Include the information specified in 40 CFR 63.182(c)(1) through (c)(3). Subpart H. [40 CFR 63.182(c)]
- 286 [40 CFR 63.182(d)] Submit Periodic Reports: Due semiannually starting 6 months after the Notification of Compliance Status, as required in 40 CFR 63.182(c). Include the information specified in 40 CFR 63.182(d)(2) through (d)(4). Subpart H. [40 CFR 63.182(d)]
- 287 [LAC 33:III.501.C.6] The number of each type of component required to be monitored for each monitoring period under applicable leak detection and repair programs shall be reported to the LDEQ by inclusion with each periodic monitoring report. Fugitive emission piping components may be added to or removed from the permitted units without triggering the need to apply for a permit modification, provided:
- a) Changes in components involve routine maintenance or are undertaken to address safety concerns, or involve small piping revisions with no associated emissions increase except from the fugitive emission components themselves;
 - b) The changes do not involve any associated increase in production rate or capacity, or tie in of new or modified process equipment other than the piping components;
 - c) Actual emissions following the changes will not exceed the emission limits contained in this permit; and
 - d) The components are promptly incorporated into any applicable leak detection or repair program.
- 288 [LAC 33:III.501] Comply with LAC 33:III.2121 by implementing the Louisiana Consolidated Fugitive Emission Program Guidelines. Compliance is achieved through compliance with 40 CFR 63 Subpart H.

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 289 [40 CFR 63.162(c)] Identify each piece of equipment in a process unit such that it can be distinguished readily from equipment that is not subject to 40 CFR 63 Subpart H. Subpart H. [40 CFR 63.162(c)]
- 290 [40 CFR 63.162(f)] Clearly identify leaking equipment, for leaking equipment detected as specified in 40 CFR 63.163, 40 CFR 63.164, 40 CFR 63.168, 40 CFR 63.169, and 40 CFR 63.172 through 63.174. The identification may be removed after the equipment is repaired, except for valves or for connectors subject to 40 CFR 63.174(c)(1)(i). The identification on a valve may be removed after it has been monitored as specified in 40 CFR 63.168(f)(3) and 63.175(e)(i)(D), and no leak has been detected during the follow-up monitoring. If electing to comply using the provisions of 40 CFR 63.174(c)(1)(i), the identification on a connector may be removed after it is monitored as specified in 40 CFR 63.174(c)(1)(i) and no leak is detected during that monitoring. Subpart H. [40 CFR 63.162(f)]
- 291 [40 CFR 63.163(b)(1)] Pumps in light liquid service: Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 monthly to detect leaks, except as provided in 40 CFR 63.162(b) and 63.163(e) through (j). If a reading of 10,000 ppm (phase I); 5,000 ppm (phase II); or 5,000 ppm (phase III, pumps handling polymerizing monomers), 2,000 ppm (phase III, pumps in food/medical service), or 1,000 ppm (phase III, all other pumps) or greater is recorded, a leak is detected. If a leak is detected, initiate repair provisions specified in 40 CFR 63.163(c). Subpart H. [40 CFR 63.163(b)(1)]
- Which Months: All Year Statistical Basis: None specified

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 292 [40 CFR 63.163(b)(3)] Pumps in light liquid service: Presence of a leak monitored by visual inspection/determination weekly (calendar). Monitor for indications of liquids dripping from the pump seal. If there are indications of liquids dripping from the pump seal, a leak is detected. If a leak is detected, initiate the repair provisions specified in 40 CFR 63.163(c). Subpart H. [40 CFR 63.163(b)(3)]
Which Months: All Year Statistical Basis: None specified
- 293 [40 CFR 63.163(c)] Pumps in light liquid service: Make a first attempt at repair no later than 5 calendar days after a leak is detected, and complete repairs no later than 15 calendar days after the leak is detected, except as provided in 40 CFR 63.163(c)(3) and 40 CFR 63.171. Subpart H. [40 CFR 63.163(c)]
- 294 [40 CFR 63.163(d)(2)] Pumps in light liquid service: Implement a quality improvement program for pumps that complies with the requirements of 40 CFR 63.176, if, in Phase III, calculated on a 6-month rolling average, the greater of either 10 percent of the pumps in a process unit or three pumps in a process unit leak. Subpart H. [40 CFR 63.163(d)(2)]
- 295 [40 CFR 63.163(d)(4)] Pumps in light liquid service: Determine percent leaking pumps using the equation in 40 CFR 63.163(d)(4). Subpart H. [40 CFR 63.163(d)(4)]
- 296 [40 CFR 63.163(e)(1)] Pumps in light liquid service (dual mechanical seal system): Operate with the barrier fluid at a pressure that is at all times greater than the pump stuffing box pressure; or equip with a barrier fluid degassing reservoir that is routed to a process or fuel gas system or connected by a closed-vent system to a control device that complies with the requirements of 40 CFR 63.172; or equip with a closed-loop system that purges the barrier fluid into a process stream. Comply with this requirement instead of the requirements in 40 CFR 63.163(a) through (d). Subpart H. [40 CFR 63.163(e)(1)]
- 297 [40 CFR 63.163(e)(2)] Pumps in light liquid service (dual mechanical seal system): Ensure that the barrier fluid is not in light liquid service. Comply with this requirement instead of the requirements in 40 CFR 63.163(a) through (d). Subpart H. [40 CFR 63.163(e)(2)]
- 298 [40 CFR 63.163(e)(3)] Pumps in light liquid service (dual mechanical seal system): Equip barrier fluid system with a sensor that will detect failure of the seal system, barrier fluid system, or both. Comply with this requirement instead of the requirements in 40 CFR 63.163(a) through (d). Subpart H. [40 CFR 63.163(e)(3)]
- 299 [40 CFR 63.163(e)(4)] Pumps in light liquid service (dual mechanical seal system): Presence of a leak monitored by visual inspection/determination weekly (calendar). Monitor for indications of liquids dripping from the pump seal. If there are indications of liquid dripping from the pump seal at the time of the weekly inspection, monitor the pump as specified in 40 CFR 63.180(b) to determine if there is a leak of organic HAP in the barrier fluid. If an instrument reading of 1,000 ppm or greater is measured, a leak is detected. If a leak is detected, initiate the repair provisions in 40 CFR 63.163(e)(6). Comply with this requirement instead of the requirements in 40 CFR 63.163(a) through (d). Subpart H. [40 CFR 63.163(e)(4)]
Which Months: All Year Statistical Basis: None specified
- 300 [40 CFR 63.163(e)(6)(i)] Pumps in light liquid service (dual mechanical seal system): Determine, based on design considerations and operating experience, criteria that indicates failure of the seal system, the barrier fluid system, or both. Comply with this requirement instead of the requirements in 40 CFR 63.163(a) through (d). Subpart H. [40 CFR 63.163(e)(6)(i)]
- 301 [40 CFR 63.163(e)(6)] Pumps in light liquid service (dual mechanical seal system): Make a first attempt at repair no later than 5 calendar days after each leak is detected, and complete repairs no later than 15 calendar days after the leak is detected, except as provided in 40 CFR 63.171. Comply with this requirement instead of the requirements in 40 CFR 63.163(a) through (d). Subpart H. [40 CFR 63.163(e)(6)]

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 302 [40 CFR 63.163(e)] Pumps in light liquid service (dual mechanical seal system - sensor): Equipment/operational data monitored by visual inspection/determination daily, or equip with an audible alarm unless the pump is located within the boundary of an unmanned plant site. If the sensor indicates failure of the seal system, the barrier fluid system, or both based on the criteria established in 40 CFR 63.163(e)(6), a leak is detected. If a leak is detected, initiate repair provisions specified in 40 CFR 63.163(e)(6). Comply with this requirement instead of the requirements in 40 CFR 63.163(a) through (d). Subpart H. [40 CFR 63.163(e)]
Which Months: All Year Statistical Basis: None specified
- 303 [40 CFR 63.163(h)] Pumps in light liquid service (unmanned plant site): Presence of a leak monitored by visual inspection/determination at the regulation's specified frequency. Monitor each pump as often as practicable and at least monthly. Comply with this requirement instead of the weekly visual inspection requirement of 40 CFR 63.163(b)(3) and (e)(4), and the daily requirements of 40 CFR 63.163(e)(5). Subpart H. [40 CFR 63.163(h)]
Which Months: All Year Statistical Basis: None specified
- 304 [40 CFR 63.163(j)(1)] Pumps in light liquid service (unsafe-to-monitor): Determine that the pump is unsafe-to-monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with 40 CFR 63.163(b) through (d). Comply with this requirement instead of the requirements in 40 CFR 63.163(b) through (e). Subpart H. [40 CFR 63.163(j)(1)]
- 305 [40 CFR 63.163(j)(2)] Pumps in light liquid service (unsafe-to-monitor): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 at the regulation's specified frequency. Maintain a written plan that requires monitoring of the pump as frequently as practicable during safe-to-monitor times but not more frequently than the periodic monitoring schedule otherwise applicable. Comply with this requirement instead of the requirements in 40 CFR 63.163(b) through (e). Subpart H. [40 CFR 63.163(j)(2)]
Which Months: All Year Statistical Basis: None specified
- 306 [40 CFR 63.164(a)] Compressors: Equip with a seal system that includes a barrier fluid system and that prevents leakage of process fluid to the atmosphere, except as provided in 40 CFR 63.162(b) and 40 CFR 63.164(h) and (i). Subpart H. [40 CFR 63.164(a)]
- 307 [40 CFR 63.164(b)] Compressors: Operate the seal system with the barrier fluid at a pressure that is greater than the compressor stuffing box pressure; or equip with a barrier fluid system degassing reservoir that is routed to a process or fuel gas system or connected by a closed-vent system to a control device that complies with the requirements of 40 CFR 63.172; or equip with a closed-loop system that purges the barrier fluid directly into a process stream. Subpart H. [40 CFR 63.164(b)]
- 308 [40 CFR 63.164(c)] Compressors: Ensure that the barrier fluid is not in light liquid service. Subpart H. [40 CFR 63.164(c)]
- 309 [40 CFR 63.164(d)] Compressors: Equip each barrier fluid system as described in 40 CFR 63.164(a) through (c) with a sensor that will detect failure of the seal system, barrier fluid system, or both. Subpart H. [40 CFR 63.164(d)]
- 310 [40 CFR 63.164(e)(2)] Compressors (sensor): Determine, based on design considerations and operating experience, a criterion that indicates failure of the seal system, the barrier fluid system, or both. Subpart H. [40 CFR 63.164(e)(2)]
- 311 [40 CFR 63.164(g)] Compressors: Make a first attempt at repair no later than 5 calendar days after each leak is detected, and complete repairs no later than 15 calendar days after each leak is detected, except as provided in 40 CFR 63.171. Subpart H. [40 CFR 63.164(g)]
- 312 [40 CFR 63.164(i)(2)] Compressors (no detectable emissions): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 once initially and annually, and at other times requested by DEQ. Comply with this requirement instead of the requirements in 40 CFR 63.164(a) through (h). Subpart H. [40 CFR 63.164(i)(2)]
Which Months: All Year Statistical Basis: None specified

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 313 [40 CFR 63.164] Compressors (sensor): Equipment/operational data monitored by visual inspection/determination daily, or equip with an alarm, unless the compressor is located within the boundary of an unmanned plant site. If the sensor indicates failure of the seal system, the barrier fluid system, or both based on the criterion determined under 40 CFR 63.164(e)(2), a leak is detected. If a leak is detected, initiate repair provisions specified in 40 CFR 63.164(g). Subpart H.
Which Months: All Year Statistical Basis: None specified
- 314 [40 CFR 63.165(a)] Pressure relief device in gas/vapor service: Organic HAP < 500 ppm above background except during pressure releases, as determined by the method specified in 63.180(c). Subpart H. [40 CFR 63.165(a)]
Which Months: All Year Statistical Basis: None specified
- 315 [40 CFR 63.165(b)(1)] Pressure relief devices in gas/vapor service: After each pressure release, return to a condition indicated by an instrument reading of less than 500 ppm above background, as soon as practicable, but no later than 5 calendar days after each pressure release, except as provided in 40 CFR 63.171. Subpart H. [40 CFR 63.165(b)(1)]
- 316 [40 CFR 63.165(b)(2)] Pressure relief devices in gas/vapor service: Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 within 5 days (calendar) after the pressure release and being returned to organic HAP service, to confirm the condition indicated by an instrument reading of less than 500 ppm above background, as measured by the method specified in 40 CFR 63.180(c). Subpart H. [40 CFR 63.165(b)(2)]
Which Months: All Year Statistical Basis: None specified
- 317 [40 CFR 63.165(d)(2)] Pressure relief devices in gas/vapor service (rupture disk): After each pressure release, install a new rupture disk upstream of the pressure relief device as soon as practicable, but no later than 5 calendar days after each pressure release, except as provided in 40 CFR 63.171. Comply with this requirement instead of the requirements in 40 CFR 63.165(a) and (b). Subpart H. [40 CFR 63.165(d)(2)]
- 318 [40 CFR 63.166] Sampling connection systems: Equip with a closed-purge, closed-loop, or closed-vent system, except as provided in 40 CFR 63.162(b). Operate the system as specified in 40 CFR 63.166(b). Subpart H.
- 319 [40 CFR 63.167] Open-ended valves or lines: Equip with a cap, blind flange, plug, or a second valve, except as provided in 40 CFR 63.162(b) and 40 CFR 63.167(d) and (e). Ensure that the cap, blind flange, plug or second valve seals the open end at all times except during operations requiring process fluid flow through the open-ended valve or line, or during maintenance or repair. Operate each open-ended valve or line equipped with a second valve in a manner such that the valve on the process fluid end is closed before the second valve is closed. Subpart H.
- 320 [40 CFR 63.168(c)] Valves in gas/vapor service or light liquid service (Phase I): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 quarterly, as specified in 40 CFR 63.180(b). If an instrument reading of 10,000 ppm or greater is recorded, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.168(f). Subpart H. [40 CFR 63.168(c)]
Which Months: All Year Statistical Basis: None specified
- 321 [40 CFR 63.168(c)] Valves in gas/vapor service or light liquid service (Phase II): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 quarterly, as specified in 40 CFR 63.180(b). If an instrument reading of 500 ppm or greater is recorded, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.168(f). Subpart H. [40 CFR 63.168(c)]
Which Months: All Year Statistical Basis: None specified

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 322 [40 CFR 63.168(d)(1)] Valves in gas/vapor service or light liquid service (Phase III, 2 percent or greater leaking valves): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 monthly, as specified in 40 CFR 63.180(b); or implement a quality improvement program for valves that complies with the requirements of 40 CFR 63.175 and monitor quarterly. If an instrument reading of 500 ppm or greater is recorded, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.168(f). If electing to implement a quality improvement program, follow the procedures in 40 CFR 63.175. Subpart H. [40 CFR 63.168(d)(1)]
Which Months: All Year Statistical Basis: None specified
- 323 [40 CFR 63.168(d)(2)] Valves in gas/vapor service or light liquid service (Phase III, less than 2 percent leaking valves): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 quarterly, as specified in 40 CFR 63.180(b). If an instrument reading of 500 ppm or greater is recorded, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.168(f). Permittee may elect to comply with the alternate standards in 40 CFR 63.168(d)(3) and (d)(4). Subpart H. [40 CFR 63.168(d)(2)]
Which Months: All Year Statistical Basis: None specified
- 324 [40 CFR 63.168(e)(1)] Valves in gas/vapor service or light liquid service: Determine percent leaking valves using the equation in 40 CFR 63.168(e)(1). Subpart H. [40 CFR 63.168(e)(1)]
- 325 [40 CFR 63.168(f)(3)] Valves in gas/vapor service or light liquid service (after leak repair): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 once within three months (at least) after repair to determine whether the valve has resumed leaking. Subpart H. [40 CFR 63.168(f)(3)]
Which Months: All Year Statistical Basis: None specified
- 326 [40 CFR 63.168(f)] Valves in gas/vapor service or light liquid service: Make a first attempt at repair no later than 5 calendar days after a leak is detected, and complete repairs no later than 15 calendar days after the leak is detected, except as provided in 40 CFR 63.171. Subpart H. [40 CFR 63.168(f)]
- 327 [40 CFR 63.168(h)(1)] Valves in gas/vapor service or light liquid service (unsafe-to-monitor): Demonstrate that the valve is unsafe to monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with 40 CFR 63.168(b) through (d). Comply with this requirement instead of the requirements in 40 CFR 63.168(b) through (f). Subpart H. [40 CFR 63.168(h)(1)]
- 328 [40 CFR 63.168(h)(2)] Valves in gas/vapor service or light liquid service (unsafe-to-monitor): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 at the regulation's specified frequency. Maintain a written plan that requires monitoring of the valves as frequently as practicable during safe-to-monitor times, but not more frequently than the periodic monitoring schedule otherwise applicable. Comply with this requirement instead of the requirements in 40 CFR 63.168(b) through (f). Subpart H. [40 CFR 63.168(h)(2)]
Which Months: All Year Statistical Basis: None specified
- 329 [40 CFR 63.168(i)(1)] Valves in gas/vapor service or light liquid service (difficult-to-monitor): Demonstrate that the valve cannot be monitored without elevating the monitoring personnel more than 2 meters above a support surface or it is not accessible at anytime in a safe manner. Comply with this requirement instead of the requirements in 40 CFR 63.168(b) through (d). Subpart H. [40 CFR 63.168(i)(1)]
- 330 [40 CFR 63.168(i)(3)] Valves in gas/vapor service or light liquid service (difficult-to-monitor): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 annually. Maintain a written plan that requires monitoring of the valves at least once per calendar year. Comply with this requirement instead of the requirements in 40 CFR 63.168(b) through (d). Subpart H. [40 CFR 63.168(i)(3)]
Which Months: All Year Statistical Basis: None specified

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 331 [40 CFR 63.169(a)] Pumps, valves, connectors, and agitators in heavy liquid service; instrumentation systems; and pressure relief devices in liquid service: Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 within 5 days (calendar) if evidence of a potential leak to the atmosphere is found by visible, audible, olfactory, or any other detection method. If a reading of 10,000 ppm for agitators, 5,000 ppm for pumps handling polymerizing monomers, 2,000 ppm for all other pumps (including pumps in food/medical service), or 500 ppm for valves, connectors, instrumentation systems, and pressure relief devices, or greater is recorded, a leak is detected. If a leak is detected, initiate repair provisions specified in 40 CFR 63.169(c). Subpart H. [40 CFR 63.169(a)]
Which Months: All Year Statistical Basis: None specified
- 332 [40 CFR 63.169(c)] Pumps, valves, connectors, and agitators in heavy liquid service; instrumentation systems; and pressure relief devices in liquid service: Make a first attempt at repair no later than 5 calendar days after each leak is detected, and complete repairs no later than 15 calendar days after it each leak is detected, except as provided in 40 CFR 63.171. Subpart H. [40 CFR 63.169(c)]
- 333 [40 CFR 63.170] Surge control vessels and bottoms receivers: Equip with a closed-vent system that routes the organic vapors vented from the surge control vessel or bottoms receiver back to the process or to a control device that complies with the requirements of 40 CFR 63.172, except as provided in 40 CFR 63.162(b), or comply with the requirements of 40 CFR 63.119(b) or (c), if surge control vessel or bottoms receiver is not routed back to the process and meets the conditions specified in 40 CFR 63 Subpart H Table 2 or Table 3. Subpart H.
- 334 [40 CFR 63.172(f)(1)(i)] Closed-vent system (hard-piping): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 once initially according to the procedures in 40 CFR 63.180(b). If an instrument reading greater than 500 ppm above background is recorded, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.172(h). Subpart H. [40 CFR 63.172(f)(1)(i)]
Which Months: All Year Statistical Basis: None specified
- 335 [40 CFR 63.172(f)(1)(ii)] Closed-vent system (hard-piping): Presence of a leak monitored by visual, audible, and/or olfactory annually. If a leak is detected, initiate repair provisions in 40 CFR 63.172(h). Subpart H. [40 CFR 63.172(f)(1)(ii)]
Which Months: All Year Statistical Basis: None specified
- 336 [40 CFR 63.172(f)(2)(i)] Closed-vent system (duct work): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 once initially according to the procedures in 40 CFR 63.180(b). If an instrument reading greater than 500 ppm above background is recorded, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.172(h). Subpart H. [40 CFR 63.172(f)(2)(i)]
Which Months: All Year Statistical Basis: None specified
- 337 [40 CFR 63.172(f)(2)(ii)] Closed-vent system (duct work): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 annually according to the procedures in 40 CFR 63.180(b). If an instrument reading greater than 500 ppm above background is recorded, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.172(h). Subpart H. [40 CFR 63.172(f)(2)(ii)]
Which Months: All Year Statistical Basis: None specified
- 338 [40 CFR 63.172(h)] Make a first attempt at repair no later than 5 calendar days after each leak is detected, and complete repairs no later than 15 calendar days after it each leak is detected, except as provided in 40 CFR 63.172(i). Subpart H. [40 CFR 63.172(h)]
- 339 [40 CFR 63.172(j)(1)] Closed-vent system (bypass lines): Flow monitored by flow indicator once every 15 minutes. Install flow indicator at the entrance to any bypass line. Subpart H. [40 CFR 63.172(j)(1)]
Which Months: All Year Statistical Basis: None specified
- 340 [40 CFR 63.172(j)(1)] Closed-vent system (bypass lines): Flow recordkeeping by electronic or hard copy once every 15 minutes. Generate records as specified in 40 CFR 63.118(a)(3). Subpart H. [40 CFR 63.172(j)(1)]

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 341 [40 CFR 63.172(j)(2)] Closed-vent system (bypass lines): Seal or closure mechanism monitored by visual inspection/determination monthly to ensure the valve is maintained in the non-diverting position and the vent stream is not diverted through the bypass line. Subpart H. [40 CFR 63.172(j)(2)]
Which Months: All Year Statistical Basis: None specified
- 342 [40 CFR 63.172(j)(2)] Closed-vent system (bypass lines): Secure the bypass line valve in the non-diverting position with a car-seal or a lock-and-key type configuration. Subpart H. [40 CFR 63.172(j)(2)]
- 343 [40 CFR 63.172(k)(1)] Closed-vent system (unsafe-to-inspect): Demonstrate that the equipment is unsafe to inspect because inspecting personnel would be exposed to an imminent or potential dangers as a consequence of complying with 40 CFR 63.172(f)(1) or (f)(2). Comply with this requirement instead of the requirements in 40 CFR 63.172(f)(1) and (f)(2). Subpart H. [40 CFR 63.172(k)(1)]
- 344 [40 CFR 63.172(k)(2)] Closed-vent system (unsafe-to-inspect): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 at the regulation's specified frequency. Maintain a written plan that requires inspection of the equipment as frequently as practicable during safe-to-inspect times, but not more frequently than annually. Comply with this requirement instead of the requirements in 40 CFR 63.172(f)(1) and (f)(2). Subpart H. [40 CFR 63.172(k)(2)]
Which Months: All Year Statistical Basis: None specified
- 345 [40 CFR 63.172(l)(1)] Closed-vent system (difficult-to-inspect): Demonstrate that the equipment cannot be inspected without elevating the inspecting personnel more than 2 meters above a support surface. Comply with this requirement instead of the requirements in 40 CFR 63.172(f)(1) and (f)(2). Subpart H. [40 CFR 63.172(l)(1)]
- 346 [40 CFR 63.172(l)(2)] Closed-vent system (difficult-to-inspect): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 once every five years. Maintain a written plan that requires inspection of the equipment at least once every five years. Comply with this requirement instead of the requirements in 40 CFR 63.172(f)(1) and (f)(2). Subpart H. [40 CFR 63.172(l)(2)]
Which Months: All Year Statistical Basis: None specified
- 347 [40 CFR 63.172(m)] Ensure that the closed-vent system or control device is operating whenever organic HAP emissions are vented to the closed-vent system or control device. Subpart H. [40 CFR 63.172(m)]
- 348 [40 CFR 63.173(a)] Agitators in gas/vapor service or light liquid service: Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 monthly to detect leaks, as specified in 40 CFR 63.180(b). If an instrument reading of 10,000 ppm or greater is recorded, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.173(c). Subpart H. [40 CFR 63.173(a)]
Which Months: All Year Statistical Basis: None specified
- 349 [40 CFR 63.173(b)] Agitators in gas/vapor service or light liquid service: Presence of a leak monitored by visual inspection/determination weekly (calendar) for indications of liquids dripping from the agitator. If there are indications of liquids dripping from the agitator, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.173(c). Subpart H. [40 CFR 63.173(b)]
Which Months: All Year Statistical Basis: None specified
- 350 [40 CFR 63.173(c)] Agitators in gas/vapor service or light liquid service: Make a first attempt at repair no later than 5 calendar days after each leak is detected, and complete repairs no later than 15 calendar days after it each leak is detected, except as provided in 40 CFR 63.171. Subpart H. [40 CFR 63.173(c)]

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 351 [40 CFR 63.173(d)(1)] Agitators in gas/vapor service and light liquid service (dual mechanical seal system): Operate with the barrier fluid at a pressure that is at all times greater than the agitator stuffing box pressure; or equip with a barrier fluid degassing reservoir that is routed to a process or fuel gas system or connected by a closed-vent system to a control device that complies with the requirements of 40 CFR 63.172; or equip with a closed-loop system that purges the barrier fluid into a process stream. Comply with this requirement instead of the requirements in 40 CFR 63.173(a). Subpart H. [40 CFR 63.173(d)(1)]
- 352 [40 CFR 63.173(d)(2)] Agitators in gas/vapor service and light liquid service (dual mechanical seal system): Ensure that the barrier fluid is not in light liquid organic HAP service. Comply with this requirement instead of the requirements in 40 CFR 63.173(a). Subpart H. [40 CFR 63.173(d)(2)]
- 353 [40 CFR 63.173(d)(3)] Agitators in gas/vapor service and light liquid service (dual mechanical seal system): Equip barrier fluid system with a sensor that will detect failure of the seal system, barrier fluid system, or both. Comply with this requirement instead of the requirements in 40 CFR 63.173(a). Subpart H. [40 CFR 63.173(d)(3)]
- 354 [40 CFR 63.173(d)(4)] Agitators in gas/vapor service or light liquid service (dual mechanical seal system): Presence of a leak monitored by visual inspection/determination weekly (calendar). Monitor for indications of liquids dripping from the agitator seal. If there are indications of liquid dripping from the agitator seal at the time of the weekly inspection, monitor the agitator as specified in 40 CFR 63.180(b) to determine the presence of organic HAP in the barrier fluid. If an instrument reading of 10,000 ppm or greater is measured, a leak is detected. If a leak is detected, initiate the repair provisions in 40 CFR 63.173(d)(6). Comply with this requirement instead of the requirements in 40 CFR 63.173(a). Subpart H. [40 CFR 63.173(d)(4)]
Which Months: All Year Statistical Basis: None specified
- 355 [40 CFR 63.173(d)(6)(i)] Agitators in gas/vapor service and light liquid service (dual mechanical seal system): Determine, based on design considerations and operating experience, criteria that indicates failure of the seal system, the barrier fluid system, or both. Comply with this requirement instead of the requirements in 40 CFR 63.173(a). Subpart H. [40 CFR 63.173(d)(6)(i)]
- 356 [40 CFR 63.173(d)(6)] Agitators in gas/vapor service and light liquid service (dual mechanical seal system): Make a first attempt at repair no later than 5 calendar days after each leak is detected, and complete repairs no later than 15 calendar days after the leak is detected, except as provided in 40 CFR 63.171. Comply with this requirement instead of the requirements in 40 CFR 63.173(a). Subpart H. [40 CFR 63.173(d)(6)]
- 357 [40 CFR 63.173(d)] Agitators in gas/vapor service or light liquid service (dual mechanical seal system - sensor): Equipment/operational data monitored by visual inspection/determination daily, or equip with an audible alarm unless the agitator is located within the boundary of an unmanned plant site. If the sensor indicates failure of the seal system, the barrier fluid system, or both based on the criteria established in 40 CFR 63.173(d)(6), a leak is detected. If a leak is detected, initiate repair provisions specified in 40 CFR 63.173(d)(6). Comply with this requirement instead of the requirements in 40 CFR 63.173(a). Subpart H. [40 CFR 63.173(d)]
Which Months: All Year Statistical Basis: None specified
- 358 [40 CFR 63.173(g)] Agitators in gas/vapor service or light liquid service (unmanned plant site): Presence of a leak monitored by visual inspection/determination at the regulation's specified frequency. Monitor each agitator as often as practicable and at least monthly. Comply with this requirement instead of the weekly visual inspection requirement of 40 CFR 63.173(b)(1) and (d)(4), and the daily requirements of 40 CFR 63.173(d)(5). Subpart H. [40 CFR 63.173(g)]
Which Months: All Year Statistical Basis: None specified
- 359 [40 CFR 63.173(h)(1)] Agitators in gas/vapor service or light liquid service (difficult to monitor): Demonstrate that the agitator cannot be monitored without elevating the monitoring personnel more than two meters above a support surface or it is not accessible at anytime in a safe manner. Comply with this requirement instead of the requirements in 40 CFR 63.173(a) through (d). Subpart H. [40 CFR 63.173(h)(1)]

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 360 [40 CFR 63.173(h)(3)] Agitators in gas/vapor service or light liquid service (difficult-to-monitor): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 annually. Maintain a written plan that requires monitoring of the agitator at least once per calendar year. Comply with this requirement instead of the requirements in 40 CFR 63.173(a) through (d). Subpart H. [40 CFR 63.173(h)(3)]
Which Months: All Year Statistical Basis: None specified
- 361 [40 CFR 63.173(j)(1)] Agitators in gas/vapor service or light liquid service (unsafe-to-monitor): Demonstrate that the agitator is unsafe to monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with 40 CFR 63.173(a) through (d). Comply with this requirement instead of the requirements in 40 CFR 63.173(a) through (d). Subpart H. [40 CFR 63.173(j)(1)]
- 362 [40 CFR 63.173(j)(2)] Agitators in gas/vapor service or light liquid service (unsafe-to-monitor): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 at the regulation's specified frequency. Maintain a written plan that requires monitoring of the agitator as frequently as practicable during safe-to-monitor times, but not more frequently than the periodic monitoring schedule otherwise applicable. Comply with this requirement instead of the requirements in 40 CFR 63.173(a) through (d). Subpart H. [40 CFR 63.173(j)(2)]
Which Months: All Year Statistical Basis: None specified
- 363 [40 CFR 63.174(b)(1)] Connectors in gas/vapor service or light liquid service: Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 once within 12 months after the compliance date, except as provided in 40 CFR 63.174(f) through (h). If an instrument reading of 500 ppm or greater is recorded, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.174(d). Subpart H. [40 CFR 63.174(b)(1)]
Which Months: All Year Statistical Basis: None specified
- 364 [40 CFR 63.174(b)(2)] Connectors in gas/vapor service or light liquid service: Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 once within the first 12 months after initial startup or by no later than 12 months after the date of promulgation of a specific subpart that references 40 CFR 63 Subpart H, whichever is later, except as specified in 40 CFR 63.174(f) through (h). If an instrument reading of 500 ppm or greater is recorded, a leak is detected. If a leak is detected, initiate repair provisions in 40 CFR 63.174(d). Subpart H. [40 CFR 63.174(b)(2)]
Which Months: All Year Statistical Basis: None specified
- 365 [40 CFR 63.174(b)(3)(i)] Connectors in gas/vapor service or light liquid service (0.5% or greater leaking): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 annually. Subpart H. [40 CFR 63.174(b)(3)(i)]
Which Months: All Year Statistical Basis: None specified
- 366 [40 CFR 63.174(b)(3)(ii)] Connectors in gas/vapor service or light liquid service (less than 0.5% leaking): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 once every two years. Subpart H. [40 CFR 63.174(b)(3)(ii)]
Which Months: All Year Statistical Basis: None specified
- 367 [40 CFR 63.174(c)(1)(i)] Connectors in gas/vapor service or light liquid service (opened or otherwise had the seal broken): Presence of a leak monitored by 40 CFR 60, Appendix A, Method 21 within three months after being returned to organic HAP service or when it is reconnected. If monitoring detects a leak, repair according to the provisions of 40 CFR 63.174(d), as specified, except as provided in 40 CFR 63.174(c)(1)(ii). Subpart H. [40 CFR 63.174(c)(1)(i)]
Which Months: All Year Statistical Basis: None specified
- 368 [40 CFR 63.174(c)(2)(i)] Connectors in gas/vapor service or light liquid service (2 inches or less in nominal diameter): Comply with the requirements of 40 CFR 63.169. Subpart H. [40 CFR 63.174(c)(2)(i)]

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 369 [40 CFR 63.174(c)(2)(ii)] Connectors in gas/vapor service or light liquid service (2 inches or less in nominal diameter): Organic HAP monitored by technically sound method within three months after being returned to organic HAP service after having been opened or otherwise had the seal broken. If monitoring detects a leak, implement repair provisions in 40 CFR 63.174(d). Subpart H. [40 CFR 63.174(c)(2)(ii)]
Which Months: All Year Statistical Basis: None specified
- 370 [40 CFR 63.174(d)] Connectors in gas/vapor service or light liquid service: Make a first attempt at repair no later than 5 calendar days after each leak is detected, and complete repairs no later than 15 calendar days after it each leak is detected, except as provided in 40 CFR 63.171 and 63.174(g). Subpart H. [40 CFR 63.174(d)]
- 371 [40 CFR 63.174(f)(1)] Connectors in gas/vapor service or light liquid service (unsafe-to-monitor): Demonstrate that the connector is unsafe to monitor because personnel would be exposed to an immediate danger as a result of complying with 40 CFR 63.174(a) through (c). Comply with this requirement instead of the requirements in 40 CFR 63.174(a). Subpart H. [40 CFR 63.174(f)(1)]
- 372 [40 CFR 63.174(f)(2)] Connectors in gas/vapor service or light liquid service (unsafe-to-monitor): Organic HAP monitored by 40 CFR 60, Appendix A, Method 21 at the regulation's specified frequency. Maintain a written plan that requires monitoring of connectors as frequently as practicable during safe to monitor times, but not more frequently than the periodic schedule otherwise applicable. Comply with this requirement instead of the requirements in 40 CFR 63.174(a). Subpart H. [40 CFR 63.174(f)(2)]
Which Months: All Year Statistical Basis: None specified
- 373 [40 CFR 63.174(g)] Connectors in gas/vapor service or light liquid service (unsafe-to-repair): Demonstrate that repair personnel would be exposed to an immediate danger as a consequence of complying with 40 CFR 63.174(d). Comply with this requirement instead of the requirements in 40 CFR 63.174(a), (d), and (e). Subpart H. [40 CFR 63.174(g)]
- 374 [40 CFR 63.174(h)(2)] Connectors in gas/vapor service or light liquid service (inaccessible, ceramic, or ceramic-lined): Make a first attempt at repair within 5 days after leak is detected by visual, audible, olfactory or other means, and complete repairs no later than 15 calendar days after leak is detected, except as provided in 40 CFR 63.171 and 63.174(g). Comply with this requirement instead of the monitoring requirements of 40 CFR 63.174(a) and (c) and from the recordkeeping and reporting requirements of 40 CFR 63.181 and 63.182. Subpart H. [40 CFR 63.174(h)(2)]
- 375 [40 CFR 63.174(i)] Connectors in gas/vapor service or light liquid service: Calculate percent leaking connectors as specified in 40 CFR 63.174(i)(1) and (i)(2). Subpart H. [40 CFR 63.174(i)]
- 376 [40 CFR 63.180] Comply with the test methods and procedures requirements provided in 40 CFR 63.180. Subpart H.
- 377 [40 CFR 63.181] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Maintain records as specified in 40 CFR 63.181(a) through (k). Subpart H.
- 378 [40 CFR 63.182(b)] Submit Initial Notification: Due within 120 days after the date of promulgation of the subpart that references 40 CFR 63 Subpart H. Include the information specified in 40 CFR 63.182(b)(1). Subpart H. [40 CFR 63.182(b)]
- 379 [40 CFR 63.182(b)] Submit Initial Notification: Due within 90 days after the date of promulgation of the subpart that references 40 CFR 63 Subpart H. Include the information specified in 40 CFR 63.182(b)(1). Subpart H. [40 CFR 63.182(b)]
- 380 [40 CFR 63.182(b)] Submit application: Due as soon as practicable before the construction or reconstruction is planned to commence (but it need not be sooner than 90 days after the date of promulgation of the subpart that references 40 CFR 63 Subpart H). Submit application for approval of construction or reconstruction required by 40 CFR 63.5(d) in lieu of the Initial Notification. Subpart H. [40 CFR 63.182(b)]
- 381 [40 CFR 63.182(c)] Submit Notification of Compliance Status: Due within 90 days of the compliance dates specified in the 40 CFR 63 subpart that references 40 CFR 63 Subpart H. Include the information specified in 40 CFR 63.182(c)(1) through (c)(3). Subpart H. [40 CFR 63.182(c)]

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

FUG 0002 1110-22 - ACR Process - Fugitive Emissions

- 382 [40 CFR 63.182(d)] Submit Periodic Reports: Due semiannually starting 6 months after the Notification of Compliance Status, as required in 40 CFR 63.182(c). Include the information specified in 40 CFR 63.182(d)(2) through (d)(4). Subpart H. [40 CFR 63.182(d)]
- 383 [LAC 33:III.501.C.6] The number of each type of component required to be monitored for each monitoring period under applicable leak detection and repair programs shall be reported to the LDEQ by inclusion with each periodic monitoring report. Fugitive emission piping components may be added to or removed from the permitted units without triggering the need to apply for a permit modification, provided:
- a) Changes in components involve routine maintenance or are undertaken to address safety concerns, or involve small piping revisions with no associated emissions increase except from the fugitive emission components themselves;
 - b) The changes do not involve any associated increase in production rate or capacity, or tie in of new or modified process equipment other than the piping components;
 - c) Actual emissions following the changes will not exceed the emission limits contained in this permit; and
 - d) The components are promptly incorporated into any applicable leak detection or repair program.
- 384 [LAC 33:III.501] Comply with the Louisiana Consolidated Fugitive Emission Program Guidelines. Compliance is achieved through compliance with 40 CFR 63 Subpart H.

UNF 0003 DuPont - Chloroprene Unit

- 385 [40 CFR 60.] All affected facilities shall comply with all applicable provisions in 40 CFR 60 Subpart A.
- 386 [40 CFR 61.145(b)(1)] Provide DEQ with written notice of intention to demolish or renovate prior to performing activities to which 40 CFR 61 Subpart M applies. Delivery of the notice by U.S. Postal Service, commercial delivery service, or hand delivery is acceptable. Subpart M. [40 CFR 61.145(b)(1)]
- 387 [40 CFR 61.148] Do not install or reinstall on a facility component any insulating materials that contain commercial asbestos if the materials are either molded and friable or wet-applied and friable after drying. Subpart M.
- 388 [40 CFR 61.355] Determine compliance with 40 CFR 61 Subpart FF using the test methods and procedures specified in 40 CFR 61.355(a) through (i), as applicable. Subpart FF.
- 389 [40 CFR 61.356] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency Maintain records as specified in 40 CFR 61.356(a) through (n), as applicable. Maintain each record in a readily accessible location at the facility site for a period not less than two years from the date the information is recorded unless otherwise specified. Subpart FF.
- 390 [40 CFR 61.357(a)] Submit report: Due within 90 days after January 7, 1993. Submit a report that summarizes the regulatory status of each waste stream subject to 40 CFR 61.342 and is determined by the procedures specified in 40 CFR 61.355(c) to contain benzene. Include the information specified in 40 CFR 61.357(a)(1) through (a)(4). If there is no benzene onsite in wastes, products, by-products, or intermediates, submit an initial report that is a statement to this effect. Subpart FF. [40 CFR 61.357(a)]
- 391 [40 CFR 61.357(b)] Submit report: Due whenever there is a change in the process generating the waste stream that could cause the total annual benzene quantity from facility waste to increase to 1 Mg/yr (1.1 ton/yr) or more. Submit updates to the information listed in 40 CFR 61.357(a)(1) through (a)(3). Subpart FF. [40 CFR 61.357(b)]
- 392 [40 CFR 61.] All affected facilities shall comply with all applicable provisions in 40 CFR 61 Subpart A.
- 393 [40 CFR 63.151(b)] Submit Initial Notification: Due in writing within 120 calendar days after the date of promulgation of 40 CFR 63 Subpart G. Include the information specified in 40 CFR 63.151(b)(1)(i) through (b)(1)(v). Subpart G. [40 CFR 63.151(b)]

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

UNF 0003 DuPont - Chloroprene Unit

- 394 [40 CFR 63.151(b)] Submit application for approval of construction or reconstruction required by 40 CFR 63.5(d) in lieu of an Initial Notification. Submit application as soon as practicable before construction or reconstruction is planned to commence (but it need not be sooner than 90 calendar days after the date of promulgation of 40 CFR 63 Subpart G). Include the information specified in 40 CFR 63.151(b)(1)(i) through (b)(1)(v). Subpart G. [40 CFR 63.151(b)]
- 395 [40 CFR 63.152(c)] Submit Periodic Reports: Due semiannually no later than 60 calendar days after the end of each 6-month period, except as specified in 40 CFR 63.152(c)(5) and (c)(6). Submit the first report no later than 8 months after the date the Notification of Compliance Status is due. Include the information specified in 40 CFR 63.152(c)(2) through (c)(4). Subpart G. [40 CFR 63.152(c)]
- 396 [40 CFR 63.152(f)] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records as specified in 40 CFR 63.152(f)(1) through (f)(7). Subpart G. [40 CFR 63.152(f)]
- 397 [40 CFR 63.1] All affected facilities shall comply with all applicable provisions in 40 CFR 63 Subpart A.
- 398 [40 CFR 63.2435] All affected facilities shall comply with all applicable provisions in 40 CFR 63 Subpart FFFF by the compliance date as published in the Federal Register.
- 399 [40 CFR 63.2450(a)] Be in compliance with the emission limits and work practice standards in 40 CFR 63 Subpart FFFF Tables 1 through 7 at all times, except during periods of startup, shutdown, and malfunction. Subpart FFFF. [40 CFR 63.2450(a)]
- 400 [40 CFR 63.2450(q)] Submit documentation in the precompliance report explaining why an undue safety hazard would be created if the air emission controls were installed, and describe the procedures that will be implemented to minimize HAP emissions from these vent streams, if an emission stream contains energetics or organic peroxides that, for safety reasons, cannot meet an applicable emission limit specified in 40 CFR 63 Subpart FFFF Tables 1 through 7. Subpart FFFF. [40 CFR 63.2450(q)]
- 401 [40 CFR 63.2515(a)] Submit all of the notifications in 40 CFR 63.6(h)(4) and (h)(5), 63.7(b) and (c), 63.8(e), (f)(4) and (f)(6), and 63.9(b) through (h) by the dates specified, as applicable. Subpart FFFF. [40 CFR 63.2515(a)]
- 402 [40 CFR 63.2515(c)] Submit notification of intent to conduct a performance test: Due at least 60 calendar days before the performance test is scheduled to begin as required in 40 CFR 63.7(b)(1), if required to conduct a performance test. Subpart FFFF. [40 CFR 63.2515(c)]
- 403 [40 CFR 63.2520(a)] Submit Compliance Report: Due semiannually by August 31 and February 28. Include the information specified in 40 CFR 63.2520(e)(1) through (e)(10). Subpart FFFF. [40 CFR 63.2520(a)]
- 404 [40 CFR 63.2520(a)] Submit Notification of Compliance Status Report: Due no later than 150 days after the compliance date specified in 40 CFR 63.2445. Include the information specified in 40 CFR 63.2520(d)(2)(i) through (d)(2)(ix). Subpart FFFF. [40 CFR 63.2520(a)]
- 405 [40 CFR 63.2520(a)] Submit Precompliance Report: Due at least six months prior to the compliance date. Include the information specified in 40 CFR 63.2520(c)(1) through (c)(7), as applicable. Subpart FFFF. [40 CFR 63.2520(a)]
- 406 [40 CFR 63.2525] Equipment/operational data recordkeeping by electronic or hard copy at the regulation's specified frequency. Keep records of the information specified in 40 CFR 63.2525(a) through (k), as applicable. Subpart FFFF.
- 407 [40 CFR 63.] All affected facilities shall comply with all applicable provisions in 40 CFR 63 Subpart A as delineated in Table 12 of 40 CFR 63 Subpart FFFF.
- 408 [40 CFR 68.12(b)(1)] Equipment/operational data recordkeeping by electronic or hard copy continuously. Document that the nearest public receptor is beyond the distance to a toxic or flammable endpoint defined in 68.22. [40 CFR 68.12(b)(1)]
- 409 [40 CFR 68.12(b)(2)] Complete the five-year accident history for the process as provided in 68.42. [40 CFR 68.12(b)(2)]
- 410 [40 CFR 68.12(b)(3)] Ensure that response actions have been coordinated with local emergency planning and response agencies. [40 CFR 68.12(b)(3)]

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

UNF 0003 DuPont - Chloroprene Unit

- 411 [40 CFR 68.12(b)(4)] Include in the RMP the certification specified in 68.12(b)(4). [40 CFR 68.12(b)(4)]
- 412 [40 CFR 68.150] Submit Risk Management Plan (RMP): Due no later than June 21, 1999, or three years after the date on which a regulated substance is first listed under 68.130, or the date on which a regulated substance is first present above a threshold quantity in a process. Submit in a method and format to a central point as specified by EPA prior to June 21, 1999.
- 413 [40 CFR 68.155] Provide in the RMP an executive summary that includes a brief description of the elements listed in 68.155(a) through (g).
- 414 [40 CFR 68.160] Complete a single registration form and include in the RMP. Cover all regulated substances handled in covered processes. Include in the registration the information specified in 68.160(b)(1) through (13).
- 415 [40 CFR 68.165] Submit in the RMP information one worst-case release scenario for each Program 1 process. Include the data specified in 68.165(b)(1) through (13).
- 416 [40 CFR 68.168] Submit in the RMP the information provided in 68.42(b) on each accident covered by 68.42(a).
- 417 [40 CFR 68.180] Provide in the RMP the emergency response information listed in 68.180(a) through (c).
- 418 [40 CFR 68.190(c)] Submit revised registration to EPA: Due within six months after a stationary source is no longer subject to 40 CFR 68. Indicate that the stationary source is no longer covered. [40 CFR 68.190(c)]
- 419 [40 CFR 68.190] Review and update the RMP as specified in 68.190(b) and submit it in a method and format to a central point specified by EPA prior to June 21, 1999.
- 420 [40 CFR 68.200] Maintain records supporting the implementation of 40 CFR 68 for five years unless otherwise provided.
- 421 [40 CFR 68.22] Use the endpoints specified in 68.22(a) through (g) for analyses of offsite consequences.
- 422 [40 CFR 68.25] Analyze the release scenarios in 68.25, as specified in 68.25(a) through (h).
- 423 [40 CFR 68.28] Identify and analyze at least one alternative release scenario for each regulated toxic substance held in a covered process(es) and at least one alternative release scenario to represent all flammable substances held in covered processes, as specified in 68.28(b) through (e).
- 424 [40 CFR 68.30] Estimate in the RMP the population within a circle with its center at the point of the release and a radius determined by the distance to the endpoint defined in 68.22(a).
- 425 [40 CFR 68.33] List in the RMP environmental receptors within a circle with its center at the point of the release and a radius determined by the distance to the endpoint defined in 68.22(a).
- 426 [40 CFR 68.36(b)] Submit revised RMP: Due within six months after changes in processes, quantities stored or handled, or any other aspect of the stationary source increase or decrease the distance to the endpoint by a factor of two or more. [40 CFR 68.36(b)]
- 427 [40 CFR 68.36] Review and update the offsite consequence analyses at least once every five years. Complete a revised analysis within six months if changes in processes, quantities stored or handled, or any other aspect of the stationary source might reasonably be expected to increase or decrease the distance to the endpoint by a factor of two or more.
- 428 [40 CFR 68.39] Equipment/operational data recordkeeping by electronic or hard copy continuously. Maintain the records specified in 68.39(a) through (e) on the offsite consequence analyses.
- 429 [40 CFR 68.42] Include in the five-year accident history all accidental releases from covered processes that resulted in deaths, injuries, or significant property damage on site, or known offsite deaths, injuries, evacuations, sheltering in place, property damage, or environmental damage. Include the information specified in 68.42(b)(1) through (10) for each accidental release.

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

UNF 0003 DuPont - Chloroprene Unit

- 430 [40 CFR 82.Subpart F] Comply with the standards for recycling and emissions reduction pursuant to 40 CFR Part 82, Subpart F, except as provided for Motor Vehicle Air Conditioners (MVACs) in Subpart B.
- 431 [LAC 33:III.1103] Emissions of smoke which pass onto or across a public road and create a traffic hazard by impairment of visibility as defined in LAC 33:III.111 or intensify an existing traffic hazard condition are prohibited.
- 432 [LAC 33:III.1109.B] Outdoor burning of waste material or other combustible material is prohibited.
- 433 [LAC 33:III.1303.B] Emissions of particulate matter which pass onto or across a public road and create a traffic hazard by impairment of visibility or intensify an existing traffic hazard condition are prohibited.
- 434 [LAC 33:III.2113.A] Maintain best practical housekeeping and maintenance practices at the highest possible standards to reduce the quantity of organic compounds emissions. Good housekeeping shall include, but not be limited to, the practices listed in LAC 33:III.2113.A.1-5.
- 435 [LAC 33:III.219] Failure to pay the prescribed application fee or annual fee as provided herein, within 90 days after the due date, will constitute a violation of these regulations and shall subject the person to applicable enforcement actions under the Louisiana Environmental Quality Act including, but not limited to, revocation or suspension of the applicable permit, license, registration, or variance.
- 436 [LAC 33:III.2901.D] Discharges of odorous substances at or beyond property lines which cause a perceived odor intensity of six or greater on the specified eight point butanol scale as determined by Method 41 of LAC 33:III.2901.G are prohibited.
- 437 [LAC 33:III.2901.F] If requested to monitor for odor intensity, take and transport samples in a manner which minimizes alteration of the samples either by contamination or loss of material. Evaluate all samples as soon after collection as possible in accordance with the procedures set forth in LAC 33:III.2901.G.
- 438 [LAC 33:III.501.C.6] The Permittee shall control fugitive emissions of VOC by a monitoring program conforming to LAC 33:III.2121.
- 439 [LAC 33:III.5105.A.2] Do not cause a violation of any ambient air standard listed in LAC 33:III.Table 51.2, unless operating in accordance with LAC 33:III.5109.B.
- 440 [LAC 33:III.5107.A.2] Include a certification statement with the annual emission report and revisions to any emission report that attests that the information contained in the emission report is true, accurate, and complete, and that is signed by a responsible official, as defined in LAC 33:III.502. Include the full name of the responsible official, title, signature, date of signature and phone number of the responsible official.
- 441 [LAC 33:III.5107.A] Submit Annual Emissions Report: Due annually, by the 30th of April unless otherwise directed by DEQ, to the Office of Environmental Services in a format specified by DEQ. Identify the quantity of emissions in the previous calendar year for any toxic air pollutant listed in Table 51.1 or Table 51.3.
- 442 [LAC 33:III.5151.F.1.f] An individual or company contracted to perform a demolition or renovation activity which disturbs RACM must be recognized by the Licensing Board for Contractors to perform asbestos abatement, and shall meet the requirements of LAC 33:III.5151.F.2 and F.3 for each demolition or renovation activity.
- 443 [LAC 33:III.535] Comply with the Part 70 General Conditions as set forth in LAC 33:III.535 and the Louisiana General Conditions as set forth in LAC 33:III.537. [LAC 33:III.535, LAC 33:III.537]
- 444 [LAC 33:III.5609.A.1.b] Activate the preplanned abatement strategy listed in LAC 33:III.5611.Table 5 when the administrative authority declares an Air Pollution Alert.
- 445 [LAC 33:III.5609.A.2.b] Activate the preplanned strategy listed in LAC 33:III.5611.Table 6 when the administrative authority declares an Air Pollution Warning.
- 446 [LAC 33:III.5609.A.3.b] Activate the preplanned abatement strategy listed in LAC 33:III.5611.Table 7 when the administrative authority declares an Air Pollution Emergency.

SPECIFIC REQUIREMENTS

AI ID: 38806 - E I DuPont de Nemours & Co - Pontchartrain Site

Activity Number: PER20140003

Permit Number: 3000-V5

Air - Title V Regular Permit Minor Mod

UNF 0003 DuPont - Chloroprene Unit

- 447 [LAC 33:III.5609.A] Prepare standby plans for the reduction of emissions during periods of Air Pollution Alert, Air Pollution Warning and Air Pollution Emergency. Design standby plans to reduce or eliminate emissions in accordance with the objectives as set forth in LAC 33:III.5611.Tables 5, 6, and 7.
- 448 [LAC 33:III.5901.A] Comply with the provisions in 40 CFR 68, except as specified in LAC 33:III.5901.
- 449 [LAC 33:III.5907] Identify hazards that may result from accidental releases of the substances listed in 40 CFR 68.130, Table 59.0 of LAC 33:III.5907, or Table 59.1 of LAC 33:III.5913 using appropriate hazard assessment techniques, design and maintain a safe facility, and minimize the off-site consequences of accidental releases of such substances that do occur.
- 450 [LAC 33:III.5911.A] Submit registration: Due January 31, 1998, or within 60 days after the source becomes subject to LAC 33:III.Chapter 59, whichever is later. Include the information listed in LAC 33:III.5911.B, and submit to the Office of Environmental Compliance.
- 451 [LAC 33:III.5911.C] Submit amended registration: Due to the Office of Environmental Compliance within 60 days after the information in the submitted registration is no longer accurate.
- 452 [LAC 33:III.919.F] Submit Emission Inventory (EI)/Annual Emissions Statement: Due annually, by the 30th of April for the period January 1 to December 31 of the previous year unless otherwise directed. Submit emission inventory data in the format specified by the Office of Environmental Services. Include all data applicable to the emissions source(s), as specified in LAC 33:III.919.A-G.
- 453 [LAC 33:III.927] Report the unauthorized discharge of any air pollutant into the atmosphere in accordance with LAC 33:I.Chapter 39, Notification Regulations and Procedures for Unauthorized Discharges. Submit written reports to the department pursuant to LAC 33:I.3925. Submit timely and appropriate follow-up reports detailing methods and procedures to be used to prevent similar atmospheric releases.
-